Printing date 06.08.2013

Version number 23

Revision: 06.08.2013

0	06.08.2013 Version number 23	Revision: 06.08.2013
⁴ 1 Identific	cation of the substance/mixture and of the company/undertaking	
· Product	identifier	
· Relevant Gas can f	ame: <u>Hilti GC21</u> identified uses of the substance or mixture and uses advised against for use exclusively with the Hilti GX 120 tool. ion of the substance / the preparation Propellant for direct fastening tools.	
• Manufac Hilti Fran Rond Poin 1, rue Jea 78778 Ma Tel +33 1	f the supplier of the safety data sheet eturer/Supplier: nce S.A. nt Mérantais an Mermoz agny-les-Hameaux I 3012 5000 1 3012 5012	
Customer Tel : 082 Fax : 082		
• Informin df-hse@h see sectio • Emergen Schweize	ng department: nilti.com	
Paris: 01 Marseille Nancy: 03	nti-Poisons Permanence médicale téléphonique : 40 05 48 48 Lyon: 04 72 11 69 11 e: 04 91 75 25 25 Lille: 0 825 812 822 3 83 32 36 36 Angers: 02 41 48 21 21 w.centres-antipoison.net	
2 Hazards	s identification	
	ation of the substance or mixture ation according to Regulation (EC) No 1272/2008 GHS02 flame	
	rosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if he ation according to Directive 67/548/EEC or Directive 1999/45/EC	ated.
R12: E	; Extremely flammable	
The produce of the EU	tion concerning particular hazards for human and environment: uct has to be labelled due to the calculation procedure of the "General Classification guide " in the latest valid version. Pressurized container.	
The produ		
GHS02		
· Hazard s	ord Danger statements 29 Extremely flammable aerosol. Pressurised container: May burst if heated.	(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31 / ISO 11014

Printing date 06.08.2013

Version number 23

Revision: 06.08.2013

Trade name: Hilti GC21

· Precautionary statements

- P102 Keep out of reach of children.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture of the substances listed below with harmless additions.

CAS: 75-28-5 isobutane 5	50-<75%
EINECS: 200-857-2 F + R12	
Reg.nr.: 01-2119485395-27 🐼 Flam. Gas 1, H220; 🔗 Press. Gas, H280	
CAS: 115-07-1 propene 12	2,5-<20%
EINECS: 204-062-1 F + R12	
🐼 Flam. Gas 1, H220; 🔗 Press. Gas, H280	
CAS: 74-98-6 propane liquefied	5-<10%
EINECS: 200-827-9 F+ R12	
Reg.nr.: 01-2119486944-21 🐼 Flam. Gas 1, H220; 🔗 Press. Gas, H280	
CAS: 106-97-8 butane, pure 2	2,5-<5%
EINECS: 203-448-7 F + R12	
Reg.nr.: 01-2119474691-32 🐼 Flam. Gas 1, H220; 🔗 Press. Gas, H280	

· Additional information

Gas can with 2 chambers:

1. Propane / butane (pressure gas) - remains in the can after use

2. Isobutane, dimethylether, ethanol, propylene, mineral oil (active agent), Buta-1,3-diene content less than 0,1%

For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- After inhalation
- Take affected persons into the open air and position comfortably
- In case of unconsciousness bring patient into stable side position for transport.
- After skin contact Instantly wash with water and soap and rinse thoroughly. If skin irritation persist, call a physician.
- After eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- · After swallowing Seek immediate medical advice.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents Water spray, carbon dioxide (CO2), carbon dioxide blanket, foam, or dry powder.
- · For safety reasons unsuitable extinguishing agents Water with full jet.
- · Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire. Burning produces irritant fumes

(Contd. on page 3)

(Contd. of page 1)

Safety data sheet

according to 1907/2006/EC, Article 31 / ISO 11014

Printing date 06.08.2013

Version number 23

Revision: 06.08.2013

(Contd. of page 2)

Trade name: Hilti GC21

- · Advice for firefighters
- · Protective equipment: In the event of fire, wear self contained breathing apparatus EN 12941 / EN 12942

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Bring persons out of danger. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Keep away from ignition sources **Environmental precautions:** Do not allow product to reach sewage system or water bodies. Inform respective authorities in case product reaches water or sewage system. Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Dispose of contaminated material as waste according to item 13. **Reference to other sections**
- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for information on disposal.

7 Handling and storage

· Handling

- · Precautions for safe handling
- Keep away from heat and direct sunlight.

Provide sufficient air exchange and/or exhaust in work rooms. When using, do not eat, drink or smoke. Ingestion, exposure to skin and eyes and inhalation of any general vapours should be avoided.

- Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.

Do not spray on flames or red-hot objects.

Protect against electrostatic charges.

Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use.

- · Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and containers:
- Keep in a cool, dry and dark place; 5 °C to 25 °C.

Keep out of reach of children. Keep containers dry and tightly closed to avoid moisture absorption and contamination.

- · Information about storage in one common storage facility: Do not store with DX powder cartridges.
- Store away from foodstuffs.
- · Further information about storage conditions:

Do not transport in the passenger compartment or cabin of a motor vehicle. Protect from heat and direct sunlight.

- · Storage class 2 B
- · Specific end use(s) Gas can for use exclusively with the Hilti GX 120 tool.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

106-97-8 butane, pure

- VME (France) Long-term value: 1900 mg/m³, 800 ppm
- Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 4) FR EN

Version number 23

Revision: 06.08.2013

Trade name: Hilti GC21

Printing date 06.08.2013

(Contd. of page 3) · Exposure controls · Personal protective equipment · General protective and hygienic measures The usual precautionary measures should be adhered to general rules for handling chemicals. Wash hands during breaks and at the end of the work. Do not eat, drink or smoke while working. · Breathing equipment: Not required. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation EN 374 / EN 388 · Material of gloves Butyl rubber, BR The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. · Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Safety glasses EN 166 / EN 170 · Body protection: When using setting tools, sufficient ear protection must be worn. 9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Aerosol **Colour:** Colourless Characteristic · Odour: · Odour threshold: Not determined. . 1. 1 .12

· pH-value:	Not applicable
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not applicable Not applicable, as aerosol
· Flash point:	Not applicable, as aerosol
· Inflammability (solid, gaseous)	Not applicable.
· Ignition temperature:	Not determined
· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
	(Contd. on page 5)

FR EN



Version number 23

Revision: 06.08.2013

Trade name: Hilti GC21

		(Contd. of page
Critical values for explosion:		
Lower:	1,8 Vol %	
Upper:	11,1 Vol %	
• Vapour pressure at 20 °C:	3000 hPa	
· Density at 20 °C	0,56 g/cm ³ (DIN 51757)	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
dynamic:	Not determined.	
kinematic:	Not determined.	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- \cdot Possibility of hazardous reactions
- Danger of bursting
- Reacts with oxidizing agents
- Forms explosive gas mixture with air
- \cdot Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- \cdot Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- \cdot on the skin: No irritant effect.
- on the eye: No irritant effect.
- · Sensitization: No sensitizing effect known.
- · Additional toxicological information:

Do not inhale vapours, aerosol or spray. The inhalation of large quantities of the gasses can lead to narcotic effects. Long periods of exposure or repeated exposure can present a health hazard.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) None

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects: Not determined
- · Additional ecological information:
- · General notes:
- Do not allow product to reach ground water, water bodies or sewage system.
- Generally not hazardous for water.
- Results of PBT and vPvB assessment
- **PBT:** Not applicable. • **vPvB:** Not applicable.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31 / ISO 11014

Printing date 06.08.2013

Version number 23

Revision: 06.08.2013

(Contd. of page 5)

Trade name: Hilti GC21

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

$\cdot \ \textbf{Recommendation}$

- For disposal, local regulations issued by the authorities must be observed.
- Use the entire contents of the can. Pressurizing gas and a small quantity of combustible liquefied gas remains in the can after use.

Hand over to disposers of hazardous waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

14 06 03* other solvents and solvent mixtures

16 05 04* gases in pressure containers (including halons) containing dangerous substances

15 01 04 metallic packaging

· Uncleaned packagings:

• **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

UN-Number	
ADR, IMDG, IATA	UN1950
UN proper shipping name	
ADR	UN1950 AEROSOLS
IMDG	AEROSOLS
ΙΑΤΑ	AEROSOLS, flammable
Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases. 2.1
Label	2.1
IMDG, IATA	
Class	2.1
	2.1 2.1
Class Label Packing group	
Label Packing group	
Label Packing group ADR, IMDG, IATA	2.1
Label	2.1
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant:	2.1 Void No
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user	2.1 Void
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Kemler Number:	2.1 Void No Warning: Gases.
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Kemler Number: EMS Number:	2.1 Void No Warning: Gases. 23 F-D,S-U
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Kemler Number: EMS Number:	2.1 Void No Warning: Gases. 23 F-D,S-U
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Kemler Number: EMS Number: Transport in bulk according to Annex MARPOL73/78 and the IBC Code	2.1 Void No Warning: Gases. 23 F-D,S-U II of
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Kemler Number: EMS Number: Transport in bulk according to Annex MARPOL73/78 and the IBC Code Transport/Additional information:	2.1 Void No Warning: Gases. 23 F-D,S-U II of
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Kemler Number: EMS Number: Transport in bulk according to Annex MARPOL73/78 and the IBC Code	2.1 Void No Warning: Gases. 23 F-D,S-U II of



Version number 23

Revision: 06.08.2013

Trade name: Hilti GC21

	(Contd. of page 6)
· Tunnel restriction code	D
·IMDG	
· Remarks:	LQ 1L
· UN "Model Regulation":	UN1950, UN1950 AEROSOLS, 2.1

15 Regulatory information

· Chemical safety assessment: not required.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. R12 Extremely flammable. · Department issuing data specification sheet: Hilti Entwicklungsgesellschaft mbH Hiltistrasse 6 D-86916 Kaufering Tel.: +49 8191 906310 Fax: +49 8191 90176310 df-hse@hilti.com · Contact: Mechthild Krauter Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) • * Data compared to the previous version altered. FR EN